

# *Ammarr*

®





The Model 2720, 2700, and the 1350 are Amarr's top-of-the-line high R-Value Doors. Constructed using 2" or 1 3/8" foamed-in-place polyurethane insulation which creates a strong monolithic panel that is energy efficient. The Model 2720 has a 20-gauge steel front skin that provides a perfect option for heavy industrial applications.

Each model is secured with standard 14-gauge, galvanized steel hinges. The interior skin of each section has two continuous horizontal 20-gauge reinforcing strips. The section joint is thermally broken and chemically bonded with a pressure-sensitive adhesive sealant. An EPDM rubber weather seal further enhances the performance of the joint.

#### OPTIONAL PASS DOOR



Available for Model 2700 only in door sizes up to 16'2" wide x 16' tall. Wind Load option not available.

#### WARRANTIES

- 10-year Limited Warranty on the paint and finish
- 1-year Limited Warranty on hardware
- See your dealer or visit [amarr.com](http://amarr.com) for complete warranty details

## Construction

**Model 2720** (Available Fall 2011)

Extra Heavy-duty 2" 20 Gauge Foamed-in-Place Door

**Model 2700**

Heavy-duty 2" Foamed-in-Place Door

**Model 1350**

Heavy-duty 1-3/8" Foamed-in-Place Door


\*Based upon independent laboratory test results.

\*\*Calculated door section R-value is in accordance with DASMA TDS-163.

MODEL 2720  
R-Value  
19.40\*

MODEL 2700  
R-Value  
19.40\*

MODEL 1350  
R-Value  
14.46\*\*



### TRIPLE-LAYER

#### Steel + Insulation + Steel

**Track:** All Amarr Doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow-the-Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit our website at [www.amarr.com](http://www.amarr.com).

**Hardware:** Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

**Springs:** Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

#### PANEL



**RIBBED PANEL WITH STUCCO EMBOSSMENT**  
2720 is Flush Panel with stucco embossment.



**OPTIONAL FULL-VIEW PANEL**  
Clear Anodized Aluminum, White Powder Coat, or Custom Powder Coat colors. Not available for Model 1350.

#### WINDOW OPTIONS



**26" x 13" DOUBLE INSULATED ACRYLIC WINDOWS WITH BLACK FRAME**



**24" x 6" DOUBLE INSULATED ACRYLIC WINDOWS WITH BLACK FRAME**



**24" X 12" INSULATED GLASS**

#### COLORS

Actual paint colors may vary from samples shown.



**COMMERCIAL WHITE**



**BROWN (Model 2700 only)**

The Model 2700 and 1350 use a brighter tone of white color than the 2720.

Amarr steel doors arrive pre-painted; for custom colors, exterior latex paint must be used. Visit [amarr.com](http://amarr.com) for instructions on painting.



165 Carriage Court  
Winston-Salem, NC 27105

800.503.DOOR  
[www.amarr.com](http://www.amarr.com)

FOR PRODUCT BINDER:  
1.800.503.3667

FOR TECHNICAL QUESTIONS:  
1.877.512.6277

©2011 Amarr Garage Doors

Amarr reserves the right to change specifications and designs without notice and without incurring obligations.

Amarr is a registered trademark of The Amarr Company, North Carolina, U.S.A.

Printed in USA Form #6210811/10M/HA

Amarr Garage Doors are the subject of one or more pending patents and/or U.S.A. or foreign patents.